

131 KIMAX Prewash

Power cleaner for prewash

- ▲ Outstanding cleaning performance when faced with road dirt, insects, organic contaminants and brake abrasion
- ▲ Does not damage uncoated concrete floors unlike acidic products
- ▲ Ensures optimum recycling water qualities and high rates of water recycling
- ▲ Designed to be low-foaming, thus does not create excessive foam in the basin system during high washing volumes
- ▲ Pleasant, subtle perfume
- ▲ Environmentally aware and gentle composition
- ▲ Highly economical thanks to the very strong product concentration
- ▲ Free from EDTA, NTA and phosphates



Application

Only use on alkali-resistant surfaces (e.g. undamaged, coated aluminium rims). Prior to use, see instructions provided by the material and surface manufacturer and check for material compatibility where required. Do not apply on hot surfaces.

Product is suitable for pre-dilution

Apply either undiluted or prediluted to the application with a suitable dosing device. The shelf life of diluted solutions is reduced by the storage conditions and water quality.

Pre- and intensive cleaner:

In low-pressure systems as a spray application (car \geq 1:60; truck \geq 1:20; rim \geq 1:10).
In high-pressure systems as a spray application (10–20 ml/min).

Shampoo:

In automatic car washes as brush shampoo (3–5 ml/m vehicle length).

Note

Always keep containers closed and guide suction tubes through the closure. A change in colour and clouding may occur without any loss in quality due to the natural raw materials. In case of high water temperatures (> 40 °C) and/or water hardness (> 4.5 mmol/L \approx 25 °dH), adding "316 Calciel" may be sensible to avoid the formation of limescale. Apply extensively to saturate the surface. Do not allow the cleaning solution to dry. No liability is accepted in case of incorrect and unprofessional use! Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients (according to 648/2004/EC)

Nonionic surfactants 5–15%, amphoteric surfactants < 5%, alkalis, complexing agents, water-soluble solvents, corrosion protection, dyes, fragrances.
pH value (concentrate): approx. 13.5

Classification

Classification (in concentrate): GHS05, Danger. H314 Causes severe skin burns and eye damage. P280 Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. Contains: Trideceth 5-12 / Sodium Hydroxide (INCI)

Art. No.	Packaging unit (PU)	Contents in kg	Numbers of PU per pallet
c131025	25 kg canister		24
c131073	220 L drum	236	2
c131090	1000 L container	1075	1