

# 303 Alfloc

## Allround flocculant

- ▲ Cleans neutral to alkaline wastewater and recycled water
- ▲ Very rapid flocculation
- ▲ Causes very compact sedimentation
- ▲ Considerably reduces both clouding and the CSB and BSB value
- ▲ Effective across a broad range of pH values
- ▲ Also highly effective at low temperatures
- ▲ Highly economical thanks to the very strong product concentration
- ▲ Free from complexing agents and phosphates



### Application

#### Product is not suitable for pre-dilution

Apply undiluted to the application with a suitable dosing device.

#### Water treatment:

In systems with water recycling as intensive treatment (60–100 ml/m<sup>3</sup> recycling water).

Add to all sedimentation tanks.

as on-going treatment (60–100 ml/m<sup>3</sup> resulting slop; 10–30 ml/car).

Feed the water inlet to the 1st sedimentation tank and ensure it is well-mixed.

Optimum effect at pH 7.5 - 8.0.

#### Note

Always keep containers closed and guide suction tubes through the closure. A change in colour and clouding may occur without any loss in quality due to the natural raw materials. No liability is accepted in case of incorrect and unprofessional use! Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

#### Ingredients

Flocculating agent.

pH value (concentrate): approx. 2.5

#### Classification

Classification (in concentrate): GHS05, Danger. H290 May be corrosive to metals. H318 Causes serious eye damage. P280 Wear eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Contains: Polyaluminiumchloride (INCI)

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
c303030	30 kg canister	24
c303073	220 L drum	2
c303090	1000 L container	1