

304 Hydrodes

Recycling water - odor blocker

- ▲ Combats unpleasant odours due to the oxidative effect of the oxygen
- ▲ Ideal addition for an overloaded ventilation system
- ▲ Ideally suited for use in recycling water plants
- ▲ Highly efficient, followed by rapid and complete disintegration
- ▲ Very economical thanks to maximised product concentration
- ▲ Free from chlorine and phosphate



Application

Product is not suitable for pre-dilution

Apply undiluted to the application with a suitable dosing device.

Water treatment:

In systems with water recycling as on-going treatment (25–50 ml/m³ resulting slop).

Feed the water inlet to the 1st sedimentation tank and ensure it is well-mixed. In the case of gravel filter systems, if necessary add the water inlet to the gravel filter. Optimum dosage during the last hours of operation.

Note

Always keep containers closed and guide suction tubes through the closure. Store in a cool, dark place to ensure stability. The plant manufacturer's instructions must be adhered to. No liability is accepted in case of incorrect and unprofessional use! Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients

Hydrogen peroxide solution.
pH value (concentrate): approx. 3

Classification

Classification (in concentrate): GHS05, GHS07, Danger. H302 Harmful if swallowed. H318 Causes serious eye damage. P235 Keep cool. P280 Wear protective gloves/eye protection. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. Contains: Hydrogen Peroxide (INCI)

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
c304030	30 kg canister	24