

761 Dewax PD

Paraffin wax remover, free of aromates, for new cars

- Optimised to remove paraffin protective films from new vehicles
- Even dissolves stubborn stains like tar, oil and resin
- Very gentle on aluminium trims and all conventional vehicle coatings
- Very economical thanks to maximised product concentration
- Free from alkalis, EDTA, NTA, phosphates and fragrances





Application

Apply extensively to saturate the surface. Do not applicate on hot surfaces.

Product is not water-miscible

Apply undiluted to the application with a suitable dosing device or use manually.

Paraffin wax remover:

In low-pressure systems as a spray application.

Apply undiluted and leave for approx. 30 s to take effect. After the contact time rinse thoroughly with warm high-pressure.

Note

Always keep containers closed and guide suction tubes through the closure. The plant manufacturer's instructions must be adhered to. No liability is accepted in case of incorrect and unprofessional use!

Ingredients

Water-insoluble solvents.

Classification

Classification (in concentrate): GHS08, Danger. H304 May be fatal if swallowed and enters airways. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 Do NOT induce vomiting. P405 Store locked up. EUH066 Repeated exposure may cause skin dryness or cracking. Contains: C10-12 Alkane/Cycloalkane (INCI)