DATA SHEET.

VACUUM CLEANER. ST 11 pro







G. Staehle GmbH u. Co. KG Mercedesstrasse 15 D 70372 Stuttgart Telefon +49 (0) 7 11/95 44-960 Telefax +49 (0) 7 11/95 44-941 export@columbus-clean.com www.columbus-clean.com

columbus

LOW EMISSION AND VERY VERSATILE. WITH EXTENSIVE WORKING RANGE.

ST 11 pro

() The ST11 pro has all good features requested for a professional vacuuming and combined among others the infinitely adjustment of the vacuum power plus brush vacuuming functions as an optional treatment of textile floor surfaces.

- Keyword "customised": the right attachments for diverse applications.
- Comfortably and efficient: telescopic tube infinitely adjustable as well as a 2,5 meter flexible hose and a 15 meter plug-in mains cable for a large operating radius.
- The rubber castor wheels at the front and the rubber wheels at the rear side provide for steady, low noise and secure manoeuvrability.
- Extremely low noise with only 56 dB(A), ideal for use in noise sensitive areas.
- C) Fatigue-free working: the air flow can be altered infinitely directly at the container and also at the hand tube, according to the floor conditions.
- C) Easy to transport and always tidy: the vacuum cleaner features an ergonomic handle, the plug-in mains cable in signal colour finds its place in the cable compartment or simply on the cable-hook – swiftly locked via a sliding locking mechanism.
- () Two integrated parking positions to the left or right for the combi floor tool.
- The optional electrical driven brush tool can be connected easily via the integrated socket and operated through the one-handswitch on the hand tube.
- Also suitable for hard floor coverings.
- C) Exclusively by columbus: filter bags made of fleece material classified filter class M and pretreated with "Bioneem" for antiallergical application.





ST 11 pro

LxBxH	390 x 300 x 410 mm
Working width	270 mm
Volume fleece filter bag, class M	11
Noise level (1 m)	56 dB(A)
Weight	6,7 kg
Nominal diameter	32 mm

ELECTRICAL DATA

Rated voltage	230 V
Power max.	720 W
Mains cable	15 m

SUCTION

Low pressure max.	222 mbar
Air flow max.	31 l/s
Protection class	II
Air flow regulation	mechanical

EQUIPMENT

Telescopic tube	yes
Filter basket	yes
Exhaust air filter cassette	yes/HEPA
Upholstery tool	yes
Crevice tool	yes

Filter class ST 11 pro

Fleece filter bags Bioneem	М	©
Filter basket	H7	●⊙
Protection filter motor		•
Exhaust filter		0
Exhaust filter HEPA 14	H14	•

Standard • Accessory @ Optional O Washable •

STANDARD EQUPIMENT

floor tool combi 270 mm working width	
antistatic bent tube with air regulation	
suction hose 2,5 m	
telescopic tube	
mains cable 15 m	
upholstery tool	
crevice tool	

OPTIONAL EQUIPMENT

fleece filter bag packing unit 20 pcs
power brush, air driven
exhaust air filter HEPA (H12) complete with filter frame

